

IEC 309 Range

Plugs and sockets to IEC 309 Standards



GEWISS

MULTIPLE-OUTLET SOCKETS								
INPUT					MULTIPLE-OUTLET SOCKET-OUTLETS			
	Nominal current In (A)	Nominal voltage (V)	No. poles	Ref. h	No. 2 16A socket-outlets	No. 3 16A sockets	No. 3 32A sockets	
	Without cable	110 110 ÷ 130	2P+ ÷	4	GW 64 008			
			2P+ ÷	4		GW 64 022		
			3P+ ÷	4	GW 64 009			
			3P+ ÷	4		GW 64 023		
		230 200 ÷ 250	2P+ ÷	6	GW 64 010			
			3P+ ÷	6		GW 64 024		
			3P+ ÷	6	GW 64 011			
			3P+ ÷	6		GW 64 025		
			3P+N+ ÷	9	GW 64 012			
			3P+N+ ÷	9		GW 64 026		
		400 380 ÷ 415	3P+ ÷	9	GW 64 013			
			3P+N+ ÷	6		GW 64 027		
			3P+N+ ÷	6	GW 64 014			
			3P+N+ ÷	6		GW 64 028		
	32	400 / 380 ÷ 415	3P+ ÷	6			GW 64 068	
	With cable	110 110 ÷ 130	2P+ ÷	4		GW 64 050		
			3P+ ÷	4		GW 64 051		
		230 200 ÷ 250	2P+ ÷	6		GW 64 052		
			3P+ ÷	9		GW 64 053		
		400 380 ÷ 415	3P+ ÷	9		GW 64 054		
			3P+ ÷	6		GW 64 055		
			3P+ ÷	6		GW 64 056		

MULTIPLE-OUTLET ADAPTERS								
INPUT					OUTLETS			
Nominal current In (A)	Nominal voltage (V)	No. poles	Ref. h		2P+ ÷ 230 V~	3P+ ÷ 400 V~	No. 3 sockets 3P+N ÷ 400 V~	Code
16	400 380 ÷ 415	3P+N+ ÷	6		2 x 16A		1 x 16A	GW 64 059
					1 x 16A	1 x 16A	1 x 16A	GW 64 060
32	230 200 ÷ 250	2P+ ÷	6		3 x 16A			GW 64 062
	400 380 ÷ 415	3P+N+ ÷	6		1 x 16A	1 x 16A	1 x 16A	GW 64 063
					2 x 16A		1 x 32A	GW 64 064
					1 x 32A	1 x 32A	1 x 32A	GW 64 061
63	400 380 ÷ 415	3P+N+ ÷	6		2 x 32A		1 x 63A	GW 64 065