


## EMC cable glands



## Glands - brass - EMV



Brass cable gland for shielding against interference frequencies with a screening attenuation of up to 100 dB. Contact with cable shield by means of spring washer.



## Technical data

Material	Brass, nickel-plated
Sealing ring / Sealing insert	/ TPE-V
Temperature range	-40 °C ... 135 °C
Class of protection / with GWDR	IP 68 / IP 68 - 10 bar

**Note** Length L varies according to cable diameter used

## Ordering data

Type	Thread-size	KB	Shield dia.	L/L1	SW	Qty.	Order No.
<b>metric</b>							
VG M18-MS EMV	M 18 x 1.5	6.5 - 9	3.5 - 7.5	41 / 10	24	50	1706920000
VG M20-MS EMV	M 20 x 1.5	8 - 11	4 - 8.5	41 / 10	24	50	1706940000
VG M24-MS EMV	M 24 x 1.5	14 - 18	8 - 13	43 / 11	30	5	1706930000
VG M25-MS EMV	M 25 x 1.5	14 - 18	8 - 13.5	43 / 11	30	25	1706950000
<b>PG</b>							
VG PG7/9-MS EMV	PG 7	4 - 6.5	1.5 - 4	32 / 5	17	50	1713870000
VG PG9/11-MS EMV	PG 9	6.5 - 9.5	2.5 - 6	34 / 6	20	50	1706860000
VG PG11-MS EMV	PG 11	6.5 - 9	3.5 - 7.5	41 / 10	24	50	1706870000
VG PG13,5-MS EMV	PG 13.5	8 - 11	4 - 8.5	41 / 10	24	50	1706880000
VG PG16-MS EMV	PG 16	10 - 14	8 - 13	43 / 11	30	25	1706890000
VG PG16-MS EMV	PG 16	14 - 18	8 - 13	43 / 11	30	25	1713880000
VG PG21-MS EMV	PG 21	17 - 20	12.5 - 17.5	45 / 11	35	25	1706900000
VG PG21-MS EMV	PG 21	17 - 20	12.5 - 17.5	45 / 11	35	25	1713890000
VG PG29-MS EMV	PG 29	22 - 26	15 - 21	52 / 13	40	10	1706910000
VG PG29-MS EMV	PG 29	25 - 29	22 - 25	58 / 13	50	5	1713900000
VG PG36-MS EMV	PG 36	27 - 32	24 - 30.5	54 / 9	50	10	1770410000

Further versions on request

## Glands - brass - 1/EMC




n

Cable entries

B

Brass cable gland for shielding against interference frequencies with a screening attenuation of up to 90 dB. Multiple contact with cable shield by means of contact element.



## Technical data

Material	Brass, nickel-plated
Sealing ring / Sealing insert	/ CR
Temperature range	-40 °C ... 100 °C
Class of protection / with GWDR	- / IP 68 - 5 bar

**Note** Length L varies according to cable diameter used

## Ordering data

Type	Thread-size	KB	Shield dia.	L/L1	SW	Qty.	Order No.
<b>metric</b>							
VG M12-MS 1/EMV	M 12 x 1.5	3 - 6.5	-	28.5 / 6	14	50	1909490000
VG M16-MS 1/EMV	M 16 x 1.5	4.5 - 10	-	37.3 / 7	20	50	1909500000
VG M20-MS 1/EMV	M 20 x 1.5	6 - 12	-	38.8 / 8	22	50	1909510000
VG M25-MS 1/EMV	M 25 x 1.5	11 - 17	-	42 / 8	27	25	1909520000
VG M32-MS 1/EMV	M 32 x 1.5	15 - 21	-	45 / 8	34	20	1909530000
VG M40-MS 1/EMV	M 40 x 1.5	19 - 28	-	55.1 / 9	43	10	1909540000
VG M50-MS 1/EMV	M 50 x 1.5	27 - 38	-	62.2 / 9	58	10	1909550000
VG M63-MS 1/EMV	M 63 x 1.5	34 - 44	-	71.5 / 14	64	5	1909560000

Further versions on request, Torque settings available