

44 CE RANGE

WATERTIGHT SURFACE-MOUNTING JUNCTION BOXES

CHARACTERISTICS AND ADVANTAGES



GEWISS

A WIDE RANGE READY TO USE

3 TYPE OF MATERIALS

- GW PLAST 75 - GWT 650° C
- GW PLAST 75 - GWT 960° C
- GW PLAST 120 - GWT 650° C

3 IP PROTECTION CLASS:

- IP 44, IP 55, IP 56.
- Suitable for all uses.



IMQ and RINA products certification.

NEW: GWT 960° C RANGE

WIDE RANGE OF COVERS:

Deep, shallow and transparent. The right cover for every application.



VERSIONS WITH HALOGEN-FREE MATERIAL

BOXES WITH SMOOTH SIDES
OR CABLE ENTRIES

HIGH SYNERGY

WITH TRIMMING ACCESSORIES

Using couplings, cable glands, cable entries from the 50/52 RANGE.


QUICK INSTALLATION

1/4 turn screws to open cover.

Cover cannot be lost due to hook on main screw that can be inserted in any position.

Removable cover for easy internal wiring.

Screws locked in "1" position.



ibemo Kazakhstan - 09302 Republic of Kazakhstan, West Kazakhstan Oblast, Aksai, Pramzone, BKKS office complex
Phone: +7 71133 93077; Fax: +7 71133 93074; E-Mail: info-kz@ibemo.de

44 CE RANGE

WATERTIGHT SURFACE-MOUNTING JUNCTION BOXES

SELECTION GUIDE



GEWISS

44 CE RANGE - SURFACE-MOUNTING JUNCTION BOXES

Heat resistance		GW PLAST 75 (TP 85°C)					GW PLAST 120 (TP 120°C)		
Fire resistance		GWT 650°C - UL 94 : HB ■ GWT 960°C - UL 94 : VO ■					GWT 650°C - UL 94 : HB ■		
Characteristics		IP 44 with cable entries	IP 55 1/4 turn with cable entries	IP 55 1/4 turn with smooth walls	IP 55 with cable entries	IP 56 with smooth walls	IP 56 smooth walls blank cover	IP 56 smooth walls transparent cover	
BOX BASE DIMENSIONS	Dimensions (mm)								
	Cover								
	Ø 65	shallow	GW 44 001 GW 44 051 GW 44 051R						
	Ø 80	shallow	GW 44 002 GW 44 052 GW 44 052R						
	80 x 80	shallow	GW 44 003 GW 44 053						
	100 x 100	shallow		GW 44 024 GW 44 054 GW 44 054R	GW 44 234	GW 44 004	GW 44 204 GW 44 274	GW 44 404	
		deep					GW 44 214	GW 44 414	
	120 x 80	shallow				GW 44 005 GW 44 055	GW 44 205 GW 44 275	GW 44 405	
		deep					GW 44 215	GW 44 415	
	150 x 110	shallow		GW 44 026 GW 44 056 GW 44 056R	GW 44 236	GW 44 006	GW 44 206 GW 44 276	GW 44 406	GW 44 426
		deep					GW 44 216	GW 44 416	GW 44 436
	190 x 140	shallow				GW 44 007 GW 44 057	GW 44 207 GW 44 277	GW 44 407	GW 44 427
		deep					GW 44 217	GW 44 417	GW 44 437
	240 x 190	shallow				GW 44 008 GW 44 058	GW 44 208 GW 44 278	GW 44 408	GW 44 428
		deep					GW 44 218	GW 44 418	GW 44 438
	300 x 220	shallow				GW 44 009 GW 44 059	GW 44 209 GW 44 279	GW 44 409	GW 44 429
		deep					GW 44 219	GW 44 419	GW 44 439
	380 x 300	shallow				GW 44 010 GW 44 060	GW 44 210 GW 44 280	GW 44 410	GW 44 430
		deep					GW 44 220	GW 44 420	GW 44 440
	460 x 380	shallow				GW 44 011 GW 44 061	GW 44 211 GW 44 281	GW 44 411	GW 44 431
deep						GW 44 221	GW 44 421	GW 44 441	

LEGEND: ■ GWT 650°C - UL94 : HB

■ GWT 960°C - UL94 : VO

IN BOLD : versions with halogen-free material

IN RED : versions with grey cover and red base

ibemo Kazakhstan - 09502 Republic of Kazakhstan, West Kazakhstan Oblast, Aksai, Pramzone, BKKS office complex

Phone: +7 71133 93077 ; Fax: +7 71133 93074 ; E-Mail: info-kz@ibemo.de