


P 17 Tempra® IP 44, IP 55 and IP 66 combined units

plastic surface mounting LV 16/32/63 A

16/32 A INTERLOCKED SWITCHED SOCKETS

IK 08 according to BS EN 62262 and IEC 62262

Self-extinguishing : 650 °C according to BS EN 60695-2-1 and IEC 60695-2-1
Temp. rating : -20 °C to +100 °C without protection device (switch only)

 *Technical information and dimensions (p. 39)*

Without protection 125 x 220 mm				With DIN rail 125 x 280 mm			
IP 44		IP 55		IP 44		IP 66	
							
Pack	Cat. Nos	Pack	Cat. Nos	Pack	Cat. Nos	Pack	Cat. Nos


LV



100 to 130 V 50/60 Hz	16 A	2 P + ⊥	1	0566 00	1	0566 20	1	0566 40	1	0566 60
200 to 250 V 50/60 Hz	16 A	2 P + ⊥	1	0566 01	1	0566 21	1	0566 41	1	0566 61
	32 A	2 P + ⊥	1	0566 09	1	0566 29	1	0566 49	1	0566 69
380 to 415 V 50/60 Hz	16 A	3 P + ⊥	1	0566 05	1	0566 25	1	0566 45	1	0566 65
		3 P + N + ⊥	1	0566 06	1	0566 26	1	0566 46	1	0566 66
	32 A	3 P + ⊥	1	0566 13	1	0566 33	1	0566 53	1	0566 73
		3 P + N + ⊥	1	0566 14	1	0566 34	1	0566 54	1	0566 74

63 A INTERLOCKED SWITCHED SOCKETS

IK 08 according to BS EN 62262 and IEC 62262

Self-extinguishing : 650 °C according to BS EN 60695-2-1 and IEC 60695-2-1
Temp. rating : -20 °C to +100 °C without protection device (switch only)

 *Technical information and dimensions (p. 39)*

Without protection 125 x 421 mm				With DIN rail 125 x 501 mm			
IP 66				IP 66			
							
Pack	Cat. Nos			Pack	Cat. Nos		

LV

380 to 415 V 50/60 Hz	63 A	3 P + N + ⊥	1	0589 10	1	0572 99
--------------------------	------	-------------	---	---------	---	---------



Larger self assembly and factory configured units available on request

Contact us on 0845 605 4333