





## TV, SAT AND AUDIO CABLES

	Designation	Standard	Nominal voltage [V]	Number of cores	Cross sections [mm <sup>2</sup> ]	Application
<b>COAXIAL CABLES</b>						
	RG 6/U		75	67	12.7	
	RG 8A/U	MIL-C-17	50	97	9.4	
	RG 11U		75	57	7.3	
	RG 11A/U	MIL-C-17	75	67	10.2	
	RG 58/U	JAN-C-17	53.5	94	18.4	
	RG 58C/U	MIL-C-17	50	101	21.8	
	RG 59B/U	MIL-C-17	75	67	15.8	
	RG 59B/U		75	54	16.3	
	RG 213/U	MIL-C-17	50	101	9.4	
	SAT1 – 1.65/7.0	ZN-94/FKZ-005	75	55	5.2	Coaxial cables with foamed polyethylene insulation and with aluminium foil and braiding, for satellite-receivers.
	SAT4 – 1.15/5.0	WT-91/K-371	75	59	7.8	
	SAT5 – 1.0/4.8	WT-91/K-371	75	54	9.5	
	Semi air-spaced TV coaxial cable 1,0/4,5	Refer to individual product descriptions WT-91/K-374	75	56	9.0	Semi air-spaced, low loss TV coaxial cable with cellular polyethylene insulation and copper wire braided screening.
<b>SPEAKER CABLES</b>						
	Speaker cables	Refer to individual product descriptions	300	2	0.5+4.0	Speaker cables flexible bare copper strands. Core identification: 1 core smooth, 1 core corrugated or single transparent jacket with colour stripe.



### ENAMELLED COPPER WIRES

Description	Insulating Enamel		Temperature index acc. to IEC	Standards*	Production range [mm]	
	Base enamel	Overcoat			Grade 1,2**	
<b>E 120</b>	Modified Polyvinylacetal	-	120	IEC 317 - 1 IEC 317 - 12 NEMA MW 15 - C	0.70÷4.50	Very good mechanical properties. Motors and windings of thermal class E. Oil immersed transformers. Winding subject to mechanical stresses.
<b>FL 155</b>	Modified Polyurethane		155	IEC 317 - 20 NEMA MW 79 – C ZALOM 155 SC UL No: E 129934	0.02÷2.00	Very good solderability and high thermal properties. Used in small transformers, relays, solenoids, small motors, clock coils, instruments.
<b>FLN 155</b>	Modified Polyurethane	Polyamide	155	IEC 317 - 21 NEMA MW 80 - C ZALOM 155 NSC UL No: E 129934	0.03÷2.00	Very good solderability and very good windability. Suitable for use with the automatic high-speed winding machines.
<b>HL 180</b>	Modified Polyurethane	-	180	IEC 317 - 51 NEMA MW 79 - C	0.02÷1.60	Good solderability and improved thermal properties. Used for automotive coils as relays and ignition coils, in transformers and in solenoids.
<b>HLN 180</b>	Modified Polyurethane	Polyamide	180	IEC 317 - 51 NEMA MW 80 – C ZALOM 180 NAP UL No: E 129934	0.03÷1.60	Good solderability, elevated thermal properties, and very good windability. Suitable for use with the automatic high speed winding machines.
<b>H 180</b>	Polyesterimide THEIC modified	-	180	IEC 317 - 8 NEMAMW74-C;30-C; ZALOM 180 HB UL No: E 129934	0.05÷2,00	High thermal properties and good chemical resistance. Used for the motors for household appliances, hermetic motors, dry and oil filled transformers.
<b>CX 200 C 200</b>	Modified Polyester or Polyesterimide	Amideimide	200	IEC 317 – 13 NEMA MW 35 – C ZALOM 200 DP UL No: E 129934	0.15÷4.00*	Very high thermal properties and high mechanical and chemical resistance. Used in motors and transformers, ballasts and hermetic motors. *Larger diameters are available when agreed.
<b>C 220</b>	Polyamideimide	-	220	IEC 317 - 26 NEMA MW 81 - C	0.15÷3.00	Extraordinary thermal, mechanical and chemical resistance. Used in special motors, special relays, special transformers.
<b>FLS 155</b>	Polyurethane	Polyamide	155	IEC 317 - 35 NEMA MW 29 - C	0.03÷0.08 0.15÷1.40	Solderable, self bonded windings requiring no further impregnation. Used for self supporting coils.
<b>HLS 155</b>	Polyurethane	Polyamide	180	IEC 317-35	0.03÷0.08 0.15÷1.40	Solderable, self bonded windings requiring no further impregnation. Used in TV deflection coils.
<b>HXS 180</b>	Polyesterimide	Polyamide	180	IEC 317 - 37	0.15÷0.80	Self-bonded windings requiring no further impregnation, used for self-supporting coils.
<b>CXS 200</b>	Polyesterimide + Polyamideimide	Polyamide aliphatic	200	IEC 317 – 38 MW 102-C	0.15÷0.80	Heat resistant, heat bonding wire, consisting of a double coat base varnish and self bonded overcoat. Used in TV deflection coils.

\*DIN EN 60 317...and BS EN 60 317...standards are equivalent to IEC 317.

\*\* Grade 3 is available in the range 0,15-2,00 mm